

# Technical Specification Sheet

## Classic Esquire

### Specifications

Manufacturer	: Classic Carpets
ISO 9001:2008	: Certificate No. 0495
Construction	: Level Loop Pile
Fibre Contains	: 100% Nylon
Dye Methods	: 100% Solution Dyed
Gauge	: 1/10 <sup>th</sup>
Pile Weight	: 680gms/m <sup>2</sup>
Pile Height	: 3.00mm
Installation Method	: Direct Stick, ¼ Turn Recommended
Chair Protectors	: Mandatory under chairs with castors to preserve appearance retention.
Primary Backing	: Non Woven Lutrador
Secondary Backing	: Fibre Glass Reinforced Cross Link Polymer
Size	: 50cm * 50cm
Number per box	: 20pcs (5m <sup>2</sup> )
Total Weight	: 4000gms/m <sup>2</sup>

### Performance

Wear Classification	: Commercial Heavy Duty
Warranty	: 10 Year Commercial Limited Warranties
Fire Rating	: <b>Direct Stick</b> – Tested to AS/ISO 9239-1 Suitable for <b>ALL</b> building classifications <b>Verify Building Classifications with your local building authority.</b> <i>Consult your Classic Flooring representative for specific details.</i>

### Disclaimers

1. According to international Carpet Manufacturing norms colour may differ from dye lot to within tolerance.
2. Please take note of the dye lot number on the modular carpet box before installing the product.
3. Recommended installation in accordance with **ASNZS 2455.1:2007** direct stick where suitable in accordance with Classic Flooring Australia Installation Procedures.

